

Hard Drive: CONNER: CP-3044 43MB 3.5"/SL IDE / AT



```

C P - 3 0 4 4    CONNER
NO MORE PRODUCED

                                     Native| Translation
                                     -----+-----+-----
Form                3.5"/SLIMLINE      Cylinders  1047| 980|   |
Capacity form/unform  43/      MB      Heads       2|   5|   |
Seek time / track  25.0/ 8.0 ms        Sector/track 40|  17|   |
Controller          IDE / AT           Precompensation
Cache/Buffer        8 KB LOOK-AHEAD    Landing Zone
Data transfer rate  1.500 MB/S int      Bytes/Sector  512
                  4.000 MB/S ext
Recording method    RLL 2/7
                                     operating | non-operating
                                     -----+-----
Supply voltage      5/12 V              Temperature *C    5 55 |   -40 60
Power: sleep        0.4 W                Humidity %        8 80 |   8 80
  standby           0.5 W                Altitude km       -0.061 3.050|   12.200
  idle              2.0 W                Shock g           5   |   75
  seek              2.8 W                Rotation RPM      3557
  read/write        4.2 W                Acoustic dBA      40
  spin-up           W                   ECC Bit          INTER.ERROR CORR.
                                     MTBF h           100000
                                     Warranty Month
Lift/Lock/Park     YES                  Certificates      CSA,IEC380,IEC435,IEC950,U...
    
```

Layout

CONNER CP3044 PRODUCT MANUAL REV. II, 10/90

```

+-----+
| +-+J1                +-----+ |XX J5
| | |                 +-----+ |xx1 Power
| | |HDA              HSP CD DSP ACT |
| | |
| +-+                 |XX 40 Pin
|                     |XX Task
|                     |XX File
|                     |XX
    
```

